

EEC TYPE APPROVAL CERTIFICATE

With regard to Coupling Devices for Motor Vehicles

Concerning the type-approval of a type of a component with regard to Directive 94/20/EC.

EC Type Approval No:

<u>e24*94/20*0112*01</u>

Reason for extension:

- Increase of the D value.

- Deletion of two assembly plants.

SECTION I

0.1 Make (trade name of manufacturer): SIARR - Westfalia - Monoflex

0.2 Type and general commercial description: SI070

Non-standard coupling ball 50.

0.3 Means of identification of type, if marked on the component:

0.3.1 Location of that marking:

0.5 Name and address of manufacturer:

0.7 In the case of components and separate technical units, location and method of affixing of the EEC approval mark:

0.8 Name(s) and address(es) of assembly plants:

Make, Class, Type.

Manufacturer's plate on socket

plate.

S.I.A.R.R. SAS,

76810 Luneray, France.

Manufacturer's plate on socket

plate. Riveted.

S.I.A.R.R. SAS,

76810 Luneray,

France.

EC Type Approval No:

e24*94/20*0112*01

SECTION II

1. Additional information (where applicable): See Appendix 1.

2. Technical service responsible for carrying out the tests: TÜV SÜD AUTOMOTIVE GmbH,

Westendstraße 199, D-80686 München,

Germany.

3. Date of test report: As before and 25.07.2011.

4. Number of test report: 08-00265-CX-GBM up to Ext. 1.

5. Remarks (if any): See Appendix 1.

6. Place: Dublin.

7. Date: 27th July, 2011.

27 00059, 2011.



9. The index to the information package lodged with the competent authority that has granted type-approval, which may be obtained on request is attached.

10. Documentation: 6 Pages.

8.

Appendix 1

to EC Type Approval Certificate No.: e24*94/20*0112*01

Concerning the component type approval of mechanical coupling devices with regard to Directive 94/20/EC.

4	A 7 11. 1	
1.	Additional	information
1.	1 Lucitoriai	miormanon

1.1. Class of the type of coupling: A50-X; SI070

1.2. Categories or types of vehicles for which the device is designed or restricted:

M, N. See technical report 08-00265-CX-GBM up to Ext 01. and accompanying documentation.

1.3. Maximum D-value: **8.2 kN.**

1.4. Maximum vertical load S at the coupling point: 75 kg.

1.5 Maximum load U at the fifth wheel coupling point: N/A.

1.6 Maximum V-value: N/A.

1.7 Instructions for attachment of the coupling type to the vehicle and photographs or drawings of the fixing points at the vehicle given by the manufacturer; additional information if the use of the coupling type is restricted to special types of vehicles:

See manufacturer's documentation.

1.8 Information on the fitting of special towing brackets or mounting plates:

See manufacturer's documentation.

5. Remarks: N/A.